

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 May 2005 (06.05.2005)

PCT

(10) International Publication Number
WO 2005/040591 A1

(51) International Patent Classification⁷: **F02M 21/02**,
51/06, 61/18

[IT/IT]; Via Monte Pasubio, 10, I-42100 Reggio Emilia
(IT).

(21) International Application Number:
PCT/EP2004/003727

(74) Agents: **RIPAMONTI, Enrico et al.**; ING. A. Giambro-
cono & C. S.R.L., Via R. Pilo, 19/B, I-20129 Milano (IT).

(22) International Filing Date: 7 April 2004 (07.04.2004)

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
MI2003A001927 7 October 2003 (07.10.2003) IT


(71) Applicant (for all designated States except US): **MED
S.P.A.** [IT/IT]; Via Raffaello, 33, I-42100 Reggio Emilia
(IT).

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

(72) Inventor; and
(75) Inventor/Applicant (for US only): **LANDI, Stefano**

[Continued on next page]

(54) Title: **ELECTRICALLY OPERATED INJECTOR FOR GASEOUS FUEL**



(57) Abstract: An electrically operated injector (1) for feeding a gaseous fuel to a cylinder of an internal combustion engine, in particular for a motor vehicle, comprising an electromagnetic actuator (2) acting on a mechanical interceptor member (3) arranged to free or intercept a passage (4) for said fuel from a feed conduit (61) to a delivery conduit (5) connected to an outlet (6), between said delivery conduit (5) and said interceptor member (3) there being positioned a seal element (40). This latter is carried by said interceptor member (3) and has a shape tapering towards the delivery conduit (5) in order to effectively intercept said fuel gas passage (4) and minimize the area of impact with an annular end portion (43) of said delivery conduit (5).



Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*